

Specialist Hearing Solutions

Starkey

Specialist Hearing Solutions

Introducing Starkey Specialist hearing solutions, great options for patients looking for alternative hearing technology to open new gateways to better hearing and better health.

Contents

3... Bruckhoff BC D50

4... Bruckhoff BC D50 Junior

5... Bruckhoff BC D50 Metal Headband

6... Contact Mini

8... Contact Forte

10... Apollon

Bruckhoff BC D50

Bone Conduction Spectacles

Seeing and Hearing in one.

The La Belle patented hearing module is integrated in the glasses so is virtually invisible. Due to the normal position of glasses being maintained, the hearing system is ideally positioned whilst being unobtrusive to the wearer and to others.

No other hearing system can be worn more comfortly or discreetly.



- 16 Channels
- 6 Programs
- 128dB output power pressure level (OFL @ 90dB)
- 61dB Gain (@ 60dB)
- Frequency Range 250 - 6000Hz
- Operating Current 1.8mA
- Equivalent Input Noise 29dB
- Distortion <3%
- 4th Generation Feedback Canceler
- Layered Noise Reduction™
- Wind Noise Suppression
- MPO
- Volume Control
- Programme Push button
- Programme Switch Tones
- Low Battery Tone
- Telecoil
- 1 Microphone
- Audio Input
- In-situ Sound Generator
- BC Fit fitting software
- NOAH Vers. 4.3 and above
- NOAH Link
- First Fit
- Battery size 312 or 13

One hearing aid – for all spectacles.

- End pieces cold bendable making the position of the receiver flexible
- Change to different glasses with almost all glasses suitable.
- Only one hearing module is needed. Click on – done!!
- The glasses can also be worn without the hearing module using temple end pieces.

La Belle BC D50 Parts Guide

PRODUCT CODE	BRAND	PRODUCT DESCRIPTION	UNIT	PACK	PACK TYPE
La Belle BC D50 Bone Conduction Spectacle Adaption					
ENG93-603	Bruckoff	**Bruckhoff La Belle BC D50 Left Processor Below Spectale Adaption**	1	1	EA
ENG93-604	Bruckoff	**Bruckhoff La Belle BC D50 Right Processor Below Spectale Adaption**	1	1	EA
ENG93-605	Bruckoff	**Bruckhoff La Belle BC D50 Left Processor Above Spectale Adaption**	1	1	EA
ENG93-606	Bruckoff	**Bruckhoff La Belle BC D50 Right Processor Above Spectale Adaption**	1	1	EA

Bruckhoff BC D50 Junior

Junior Bone Conduction Headband

With La Belle BC D50 Junior you get a Hearing System that allows children to access the world of hearing in a simple way – without surgery! Junior Childrens Hearing Systems are small, light and comfortably fixed and worn in a headband. A great selection of beautiful and fashionable headbands are available, prefabricated for easy assembly. Even personal headbands can be modified to fit the junior hearing system so that the child won't do without his/her favourite headband.

Carefree hearing, carefree playing

The combination of headband and hearing module offers the child many benefits:

- Hardly noticeable • Extremely comfortable to wear • Almost invisible to others
- Always automatically positioned correctly on the head





A	Battery Flap	E	Housing Conductor
B	Locking Screw	F	Snap Fastener (upper part)
C	Trimmer TC Inside	G	Program Socket
D	Volume Control/Program Button	M	Microphone

- 16 Channels
- 4 Programs
- 116dB output power pressure level (OFL @ 90dB)
- 48dB Gain (@ 60dB)
- Frequency Range 250 - 4500Hz
- Operating Current 1.1mA
- Equivalent Input Noise 29dB
- Distortion <3%
- 4th Generation Feedback Canceler
- Layered Noise Reduction™
- Wind Noise Suppression
- MPO
- Volume Control
- Programme Push button
- Programme Switch Tones
- Low Battery Tone
- Telecoil
- 1 Microphone
- Audio Input
- In-situ Sound Generator
- BC Fit fitting software
- NOAH Vers. 4.3 and above
- NOAH Link
- First Fit
- Battery size 312 or 13

Hardly visible - but flexible in handling.

- Bending zone cold bendable - makes the position of the receiver flexible
- Easy attachment to the headband
- Bruckhoff design headbands
- Almost all elastic headbands are usable
- Child safety lock of battery compartment

La Belle BC D50 Junior Parts Guide

PRODUCT CODE	BRAND	PRODUCT DESCRIPTION	UNIT	PACK	PACK TYPE
La Belle BC D50 Junior Bone Conduction Headband					
ENG93-607	Bruckoff	**Bruckhoff La Belle Junior BC D50 - Anthracite Left** (headband inc)	1	1	EA
ENG93-608	Bruckoff	**Bruckhoff La Belle Junior BC D50 - Anthracite Right** (headband inc)	1	1	EA
ON / OFF	Bruckoff	**Bruckhoff La Belle Junior BC D50 - ON / OFF switch** (request at time of ordering)	1	1	EA
~~**ENG93-511**~~	~~Bruckoff~~	~~**Bruckhoff La Belle Junior BC D50 – Headband Black Stereo**~~	~~1~~	~~1~~	~~EA~~
~~**ENG93-512**~~	~~Bruckoff~~	~~**Bruckhoff La Belle Junior BC D50 – Headband Black Right**~~	~~1~~	~~1~~	~~EA~~
~~**ENG93-513**~~	~~Bruckoff~~	~~**Bruckhoff La Belle Junior BC D50 – Headband Black Left**~~	~~1~~	~~1~~	~~EA~~

Bruckhoff BC D50 Metal Headband

Bone Conduction Metal Headband

The innovative Headset Hearing System is light, easy to wear, fits every head and offers a natural hearing feeling. Headset Hearing Systems are a good solution when bone conduction is required.

Headset hearing systems: Put it on and done.

The patented Hearing Module is mounted on an adjustable metal bracket and resembles a Headset or Headphones. The light and subtle metal bracket can be quickly and easily adjusted to different head sizes via the two adjusters. Thus, you can place the hearing system in the perfect position in seconds.



- 16 Channels
- 6 Programs
- 128dB output power pressure level (OFL @ 90dB)
- 61dB Gain (@ 60dB)
- Frequency Range 250 - 6000Hz
- Operating Current 1.8mA
- Equivalent Input Noise 29dB
- Distortion <3%
- 4th Generation Feedback Canceler
- Layered Noise Reduction™
- Wind Noise Suppression
- MPO
- Volume Control
- Programme Push button
- Programme Switch Tones
- Low Battery Tone
- Telecoil
- 1 Microphone
- Audio Input
- In-situ Sound Generator
- BC Fit fitting software
- NOAH Vers. 4.3 and above
- NOAH Link
- First Fit
- Battery size 312 or 13

Technology at its finest: Light weight – strong in performance.

- Easy to use
- Lifelike quality sound
- Automatic adjustment of listening comprehension
- Perfect listening even in noisy environments
- Masks interference noise

La Belle BC D50 Metal Headband Parts Guide

PRODUCT CODE	BRAND	PRODUCT DESCRIPTION	UNIT	PACK	PACK TYPE
La Belle BC D50 Bone Conduction Metal Headband					
ENG93-601	Bruckoff	**Bruckhoff La Belle BC D50 - Headset Left**	1	1	EA
ENG93-602	Bruckoff	**Bruckhoff La Belle BC D50 - Headset Right**	1	1	EA
ENG93-177	Bruckoff	**Bruckhoff La Belle BC D50 - Adjustable Metal Headband**	1	1	EA

Contact Mini

Digital Bone Conduction Hearing System

Contact Mini is a digital miniature bone conduction hearing system for up to moderate hearing loss and from toddler's age upwards. The system is fitted using the specially developed software. This software contains the worlds first adaptive algorithm for bone conduction hearing aids, opening up an opportunity for an automatic initial fitting, which allows maximum flexibility. The full version includes five different coloured headbands, in three sizes, and two sizes of plastic headbands, to enable the Contact Mini to be worn from an early age through to adulthood.




Features

- 8 Channel soundprocessor (WDRC)
- 16 Equaliser bands
- First fitting algorithm for bone conductive hearing aids
- Tone generator for fine-tuning by INSITU method
- Feedback cancellation
- Noise reduction
- Low battery warning
- MPO programmable
- Tone filters (High Cut and Low Cut)
- Battery size 13
- On/Off switch via battery compartment
- Volume control per trimmer
- Different Colours
- Different sizes of conductor plates for optimal comfort


Fitting Range

Harmonic distortions: 500Hz <1% 800Hz <1% 1000Hz <0.6% 1600Hz <0.5%
Equivalent input noise level: 21.9 dBSPL
Power consumption: 1.06 mA +/- 10%
Battery life time: Approx 270h at 290mAh battery capacity



Contact Mini Technical Data

TOLERANCE OF MEASURED VALUES ± 4 dB		IEC 118-9 IEC 60318-6 Artificial Mastoid
Supply Voltage	1.35V	
Maximum Output Force Level (OFL90) MPO = Min.	Max.	114 dBOFL
	1000 Hz / HFA	108 dBOFL
	1600 Hz / HFA	102 dBOFL
Maximum Output Force Level (OFL90) MPO = Max.	Max.	84 dBOFL
	1000 Hz / HFA	79 dBOFL
	1600 Hz / HFA	72 dBOFL
Maximum Acousto-Mechanical Sensitivity Level	Max.	51 dB
	1000 Hz / HFA	47 dB
	1600 Hz / HFA	40 dB



Contact Mini Parts Guide

PRODUCT CODE	BRAND	PRODUCT DESCRIPTION	UNIT	PACK	PACK TYPE
Contact Mini Digital Bone Conduction Hearing System					
ENG94-100	BHM	Contact Mini Monaural Black (without fabric headband or hairband)	1	1	BOX
ENG94-045	BHM	Contact Mini Monaural Blue (without fabric headband or hairband)	1	1	BOX
ENG94-047	BHM	Contact Mini Monaural Red (without fabric headband or hairband)	1	1	BOX
ENG94-101	BHM	Contact Mini Binaural (without fabric headband or hairband)	1	1	BOX
ENG94-049	BHM	Contact Mini Monaural kit (five headbands & two hairbands)	1	1	BOX
	BHM	Soft Fabric headband - Babyblue 39/41	1	1	
	BHM	Soft Fabric headband - Babypink 39/41	1	1	
	BHM	Soft Fabric headband with velcro fastening - Fiery 49/51	1	1	
	BHM	Soft Fabric headband with velcro fastening - Coffee 51/53	1	1	
	BHM	Soft fabric headband with velcro fastening - Sunny 53/55	1	1	
	BHM	Medium 340mm Plastic Hairband	1	1	
	BHM	Standard 370mm Plastic Hairband	1	1	
ENG94-024	BHM	Contact Mini Binaural kit (five headbands & two hairbands)	1	1	BOX
	BHM	Soft Fabric headband - Babyblue 39/41	1	1	
	BHM	Soft Fabric headband - Babypink 39/41	1	1	
	BHM	Soft Fabric headband with velcro fastening - Fiery 49/51	1	1	
	BHM	Soft Fabric headband with velcro fastening - Coffee 51/53	1	1	
	BHM	Soft fabric headband with velcro fastening - Sunny 53/55	1	1	
	BHM	Medium 340mm Plastic Hairband	1	1	
	BHM	Standard 370mm Plastic Hairband	1	1	
Spare Parts					
ON/OFF	BHM	Contact Mini Separate On/Off Switch (to be requested at time of ordering)	1	1	EA
ENG94-043	BHM	Contact Mini Connection Cable for Hairband (black)	1	1	EA
ENG94-044	BHM	Contact Mini Connection Cable for Headband (white)	1	1	EA
Headbands					
ENG94-052	BHM	Contact Mini Soft Fabric headband with velcro fastening - White 43/45	1	1	EA
ENG94-053	BHM	Contact Mini Soft Fabric headband with velcro fastening - Fiery 49/51	1	1	EA
ENG94-054	BHM	Contact Mini Soft Fabric headband with velcro fastening - Olve 49/51	1	1	EA
ENG94-055	BHM	Contact Mini Soft Fabric headband with velcro fastening - Sunny 53/55	1	1	EA
ENG94-056	BHM	Contact Mini Soft Fabric headband with velcro fastening - Jet Black 53/55	1	1	EA
ENG94-103	BHM	Contact Mini Soft Fabric headband ideal for babies - Babypink 39/41	1	1	EA
ENG94-104	BHM	Contact Mini Soft Fabric headband ideal for babies - Babyblue 39/41	1	1	EA
ENG94-058	BHM	Contact Mini Soft Fabric headband with velcro fastening - Coffee 51/53	1	1	EA
ENG94-059	BHM	Contact Mini Soft Fabric headband with velcro fastening - Blue 51/53	1	1	EA
ENG94-261	BHM	Contact Mini Fabric Headband Flex* - Beige 35/59	1	1	EA
ENG94-259	BHM	Contact Mini Fabric Headband Flex* - Blue 35/59	1	1	EA
ENG94-260	BHM	Contact Mini Fabric Headband Flex* - Red 35/59	1	1	EA
Sportscaps					
ENG94-063	BHM	Contact Mini Sportscap Red size small	1	1	EA
ENG94-064	BHM	Contact Mini Sportscap Blue size small	1	1	EA
Decorative Parts for Electronic Housing					
~~ENG94-066~~	~~BHM~~	~~Contact Mini Decorative Part 'Football'~~	~~1~~	~~1~~	~~EA~~
~~ENG94-067~~	~~BHM~~	~~Contact Mini Decorative Part 'Panda Bear'~~	~~1~~	~~1~~	~~EA~~
~~ENG94-086~~	~~BHM~~	~~Contact Mini Decorative Part 'Mouse'~~	1	1	EA
Monaural / Binaural Bone Conduction Hairbands					
ENG94-072	BHM	Contact Mini Monaural Bone Conduction Hairband - Small Monaural Black 280mm	1	1	EA
ENG94-073	BHM	Contact Mini Monaural Bone Conduction Hairband - Medium Monaural Black 300mm	1	1	EA
ENG94-074	BHM	Contact Mini Monaural Bone Conduction Hairband - Standard Monaural Black 330mm	1	1	EA
ENG94-075	BHM	Contact Mini Monaural Bone Conduction Hairband - Large Monaural Black 360mm	1	1	EA
ENG94-076	BHM	Contact Mini Binaural Bone Conduction Hairband - Small Binaural Black 320mm	1	1	EA
ENG94-077	BHM	Contact Mini Binaural Bone Conduction Hairband - Medium Binaural Black 340mm	1	1	EA
ENG94-078	BHM	Contact Mini Binaural Bone Conduction Hairband - Standard Binaural Black 370mm	1	1	EA
ENG94-079	BHM	Contact Mini Binaural Bone Conduction Hairband - Large Binaural Black 400mm	1	1	EA

*Fabric woven dense headband with soft pad applied to inner side of electronic housing.

Contact Forte

Digital Bone Conduction Hearing System

Contact Forte is a digital, all-in-one bone conduction hearing system which compensates for mild to moderate hearing impairment, processing and amplifying sound and then transmitting it to the inner ear. The entire Contact Forte hearing system is housed in a single casing. This means no external cable connections, ensuring easy handling. It is resistant to sweat and dirt, and is water-resistant. Contact Forte can be linked to electronic devices via Bluetooth and the bone conduction receiver components have been optimised to offer a wider frequency spectrum.



Features


- All-in-one in a single housing, thus offering easy handling
- Unbeatable variety of wearing options
- Dust-protected and protected against splash water
- Audio streaming (Bluetooth Low Energy)
- App "BHM smart control" (Android/iOS)
- Programming via NOAHlink & HI-PRO
- 8 WDRC channels
- 16 band equalizer
- High-cut, low-cut, notch filter
- Tone generator for In-Situ fitting
- Adaptive feedback cancellation
- Adaptive noise reduction
- Fixed and adaptive directivity

Technical Data

- Equivalent input noise level < 26 dB rel. 20 µPa
- Processing delay < 6.5 ms
- Current consumption 1.35 mA (in silence)
- 1.60 mA (@ 65 dB SPL & 1 kHz)
- Weight, incl. battery < 15 g
- Dimensions < 35 mm x < 22 mm x < 15 mm
- Battery type 13
- Direct Audio Input

Contact Forte Technical Data

		Artificial Mastoid	Skull Simulator
Output Vibratory Force Level (@ 90 dB SPL, FOG)	**Peak**	119 dB rel. 1 µN	127 dB rel. 1 µN
	HFA	108 dB rel. 1 µN	113 dB rel. 1 µN
	1.6 kHz	107 dB rel. 1 µN	109 dB rel. 1 µN
Acousto-Mechanical Sensitivity Level (@ 50 dB SPL, FOG)	**Peak**	43 dB rel. 1 µN / 20 µPa	49 dB rel. 1 µN / 20 µPa
	HFA	34 dB rel. 1 µN / 20 µPa	37 dB rel. 1 µN / 20 µPa
	1.6 kHz	32 dB rel. 1 µN / 20 µPa	35 dB rel. 1 µN / 20 µPa
Basic Vibratory Force Level (@ 60 dB SPL, RTS)	**Peak**	100 dB rel. 1 µN	112 dB rel. 1 µN
	HFA	92 dB rel. 1 µN	96 dB rel. 1 µN
	1.6 kHz	90 dB rel. 1 µN	93 dB rel. 1 µN
Frequency Range		300 Hz – >8000 Hz	350 Hz – >8000 Hz
Total Harmonic Distortion (@ 60 dB SPL, RTS)		< 3% above 500 Hz	< 3% above 500 Hz





Contact Forte Parts Guide

PRODUCT CODE	BRAND	PRODUCT DESCRIPTION	UNIT	PACK	PACK TYPE
Contact Forte Digital Bone Conduction Hearing System					
05363-000	BHM	**Contact Forte-N / SW; Black; w / o headgear**	1	1	EA

Contact Forte Parts Guide

PRODUCT CODE	BRAND	PRODUCT DESCRIPTION	UNIT	PACK	PACK TYPE
Headbands - Textile					
05364-000	BHM	**SIZE 42-52 cm - Baby Blue**	1	1	EA
05365-000	BHM	**SIZE 42-52 cm - Baby Pink**	1	1	EA
05366-000	BHM	**SIZE 44-54 cm - Blue**	1	1	EA
05367-000	BHM	**SIZE 44-54 cm - Jet Black**	1	1	EA
05368-000	BHM	**SIZE 46-56 cm - Fiery**	1	1	EA
05369-000	BHM	**SIZE 46-56 cm - Olive**	1	1	EA
05370-000	BHM	**SIZE 48-58 cm - Blue**	1	1	EA
05371-000	BHM	**SIZE 48-58 cm - Fiery**	1	1	EA
05372-000	BHM	**SIZE 50-60 cm - Jet Black**	1	1	EA
05373-000	BHM	**SIZE 50-60 cm - Olive**	1	1	EA
Headbands - Plastic					
05385-000	BHM	**MON - Small**	1	1	EA
05386-000	BHM	**MON - Large**	1	1	EA
05387-000	BHM	**MON - Standard**	1	1	EA
05388-000	BHM	**MON - Medium**	1	1	EA
05389-000	BHM	**BIN - Large**	1	1	EA
05390-000	BHM	**BIN - Standard**	1	1	EA
05391-000	BHM	**BIN - Medium**	1	1	EA
05392-000	BHM	**BIN - Small**	1	1	EA
Softbands					
05374-000	BHM	**MON - Beige**	1	1	EA
05375-000	BHM	**MON - Blue**	1	1	EA
05376-000	BHM	**MON - Red**	1	1	EA
05377-000	BHM	**BIN - Beige**	1	1	EA
05378-000	BHM	**BIN - Blue**	1	1	EA
05379-000	BHM	**BIN - Red**	1	1	EA
Housing / Shells					
05397-000	BHM	**SHELL - Blue**	1	1	EA
05398-000	BHM	**SHELL - Red**	1	1	EA
05399-000	BHM	**SHELL - Black**	1	1	EA
05400-000	BHM	**SHELL - Baby Blue**	1	1	EA
05401-000	BHM	**SHELL - Baby Pink**	1	1	EA
~~**05403-000**~~	~~BHM~~	~~**SHELL – Black**~~	~~1~~	~~1~~	~~EA~~
~~**05404-000**~~	~~BHM~~	~~**SHELL – Blue**~~	~~1~~	~~1~~	~~EA~~
~~**05405-000**~~	~~BHM~~	~~**SHELL – Red**~~	~~1~~	~~1~~	~~EA~~
~~**05406-000**~~	~~BHM~~	~~**SHELL – Baby Blue**~~	~~1~~	~~1~~	~~EA~~
~~**05407-000**~~	~~BHM~~	~~**SHELL – Baby Pink**~~	~~1~~	~~1~~	~~EA~~
Misc. items					
05380-000	BHM	**STICKER-SET (15 pairs / box)**	1	1	BOX
05381-000	BHM	**STICKER-SET / L (30 pcs / box)**	1	1	BOX
05382-000	BHM	**STICKER-SET / R (30 pcs / box)**	1	1	BOX
05383-000	BHM	**ADHESIVE-ADAPTER LEFT**	1	1	EA
05384-000	BHM	**ADHESIVE-ADAPTER RIGHT**	1	1	EA
05402-000	BHM	**BC6-17 / NT Adapter assembly, headband contact forte**	1	1	EA
05408-000	BHM	**BC6-E22 / SER; filter, microphone / pair**	1	1	EA
05409-000	BHM	**BC6-315-1 / OL; venting frame, olive & filter, batt comp7**	1	1	EA
05410-000	BHM	**BC6-E41 / GR, socket seal / gray**	1	1	EA
05411-000	BHM	**BC6-72 / OL; socket cover / olive**	1	1	EA
05412-000	BHM	**BC6-61-1 / GR; push button cover**	1	1	EA
05413-000	BHM	**BC6-62 / SER, button pin / pair**	1	1	EA

Apollon

Digital High Power Pocket Hearing System

Apollon is a digital, high power pocket hearing instrument, useful for a wide range of hearing losses.

The standard configuration of Apollon is monaural air conduction, but can be converted to binaural air conduction or monaural/binaural bone conduction by using the appropriate accessories.

Programming of Apollon is by using the StarkeyFit2 software.

Standard colour of Apollon is anthracite.







Accessories

- External bone vibrator
- Dual cable for binaural sound


Features

- AutoFit, NAL, BC Fit (Bone conduction)
- 4 Band audio processor
- 2 Batteries size AA
- 4 Position switch (0-T-MT-M)
- Volume control
- Visual and acoustic low battery warning
- Audio input (3.5mm socket)

Additional features using the programming software StarkeyFit2 with Hi-Pro Box and industry standard, 4 pin programming cable:

- High Cut
- Low Cut
- Notch Filter
- Noise Reduction (On/Off, switchable through software)

Fitting Range



Warning for Acoustician
This device can reach sound pressure levels above 132dB SPL! If used without attention this can cause impairments of hearing.



Apollon Monaural Headband/Circlet

- Flexible headband for bone conduction receiver
- Clip for mounting bone conduction receiver
- Colour: Black

Monaural Headband/Circlet	Length A ± 5mm
SMALL - Black	280 mm
MEDIUM - Black	300 mm
STANDARD - Black	330 mm
LARGE - Black	360 mm



Apollon Binaural Headband/Circlet

- Flexible headband for bone conduction receiver
- 2 clips for mounting bone conduction receivers
- Colour: Black

Binaural Headband/Circlet	Length A ± 5mm
SMALL - Black	320 mm
MEDIUM - Black	340 mm
STANDARD - Black	370 mm
LARGE - Black	400 mm



Apollon Technical Data


TOLERANCE OF ACOUSTICAL VALUES ± 4 dB. (earphone ME 51-66 monaural)		DIN EN 60118-0 Ear Simulator	DIN EN 60118-7 2 ccm Coupler
Supply Voltage	3V		
Telecoil Sensitivity (IEC 60118-1)	109 dB. typ.		
Frequency Range (DIN 45605)		330 – 3100 Hz	230 – 2600 Hz
Reference Test Gain (60 dBSPL Input)	1600 Hz / HFA	77 dB	63 dB
Full-On Gain (50 dBSPL Input)	Max.	95 dB	92 dB
	1600 Hz / HFA	94 dB	83 dB
Maximum Output (90 dBSPL Input)	Max.	154 dB SPL	148 dB SPL
	1600 Hz / HFA	153 dB SPL	141 dB SPL

	Full on Gain settings*				Reference Test Gain settings (DIN EN 60118-0)*				Reference Test Gain settings (DIN EN 60118-7)*			
	Low	Mid1	Mid2	High	Low	Mid1	Mid2	High	Low	Mid1	Mid2	High
G[80]	26	24	18	8	26	24	18	8	26	24	18	8
G[50]	46	44	38	28	28	28	28	28	26	24	18	8

*Settings according software BHMFit2-Version 2.1 and higher


Monaural Technical Data

TOLERANCE OF ACOUSTIC VALUES ± 4dB			
Current drain	15.6 mA (U_B = 3 V)		
Max. acoust. - mech. sensitivity level	1000 Hz	1600 Hz	Max.
DIN EN 118-9	57 dB	56 dB	64 dB
Max. output force level (OFL90). MPO min.	1000 Hz	1600 Hz	Max.
DIN EN 118-9	120 dBOFL	119 dBOFL	125 dBOFL
Max. output force level (OFL90). MPO max.	1000 Hz	1600 Hz	Max.
DIN EN 118-9	101 dBOFL	100 dBOFL	107 dBOFL



Binaural Technical Data

TOLERANCE OF ACOUSTIC VALUES ± 4dB			
Current drain	9.2 mA (U_B = 3 V)		
Max. acoust. - mech. sensitivity level	1000 Hz	1600 Hz	Max.
DIN EN 118-9	48 dB	47 dB	55 dB
Max. output force level (OFL90). MPO min.	1000 Hz	1600 Hz	Max.
DIN EN 118-9	111 dBOFL	110 dBOFL	116 dBOFL
Max. output force level (OFL90). MPO max.	1000 Hz	1600 Hz	Max.
DIN EN 118-9	92 dBOFL	91 dBOFL	97 dBOFL



Apollon Parts Guide

PRODUCT CODE	BRAND	PRODUCT DESCRIPTION	UNIT	PACK	PACK TYPE
Apollon Body Worn Aid - Air Conduction					
ENG94-001	BHM	Apollon AIR CONDUCTION Pocket Hearing Aid	1	1	EA
Apollon Body Worn Aid - Air Conduction Spares					
ENG94-002	BHM	AIR CONDUCTION Earphone	1	1	EA
ENG94-102	BHM	AIR CONDUCTION Monaural Cable	1	1	EA
ENG94-003	BHM	AIR CONDUCTION Binaural Cable	1	1	EA
Apollon Body Worn Aid - Bone Conduction					
ENG94-001	BHM	Apollon BONE CONDUCTION Pocket Hearing Aid	1	1	EA
Apollon Body Worn Aid - Bone Conduction Spares					
ENG94-005	BHM	BONE CONDUCTION Monaural Headband & Bone Vibrator	1	1	EA
ENG94-006	BHM	BONE CONDUCTION Binaural Headband 2 x Bone Vibrators & Binaural Cable	1	1	EA
ENG94-004	BHM	BONE CONDUCTION External Bone Vibrator Single	1	1	EA
ENG94-003	BHM	BONE CONDUCTION Binaural Cable	1	1	EA
Apollon Body Worn Aid - Bone Conduction Monaural Headband/Circlet					
ENG94-009	BHM	BONE CONDUCTION Small Monaural Headband/Circlet - Black	1	1	EA
ENG94-010	BHM	BONE CONDUCTION Medium Monaural Headband/Circlet - Black	1	1	EA
ENG94-011	BHM	BONE CONDUCTION Standard Monaural Headband/Circlet - Black	1	1	EA
ENG94-012	BHM	BONE CONDUCTION Large Monaural Headband/Circlet - Black	1	1	EA
Apollon Body Worn Aid - Bone Conduction Binaural Headband/Circlet					
ENG94-013	BHM	BONE CONDUCTION Small Binaural Headband/Circlet - Black	1	1	EA
ENG94-014	BHM	BONE CONDUCTION Medium Binaural Headband/Circlet - Black	1	1	EA
ENG94-015	BHM	BONE CONDUCTION Standard Binaural Headband/Circlet - Black	1	1	EA
ENG94-016	BHM	BONE CONDUCTION Large Binaural Headband/Circlet - Black	1	1	EA


Please Note: If no circlet size is specified on the order, the standard size will be supplied. Apollon pocket hearing aid is warranted for 2 years from the date of purchase.

Contact Us

Scotland
Margaret Black
Mobile: **07894 608 206**
Email: **margaret_black@starkey.co.uk**

North & North West
Sarah Fletcher
Mobile: **07968 108 768**
Email: **sarah_fletcher@starkey.co.uk**

Ireland
Margaret Black
Mobile: **07894 608 206 | 1800 992197 (ie)**
Email: **margaret_black@starkey.co.uk**



Central & South Wales
Kiran Sihota
Mobile: **07384 216 005**
Email: **kiran_sihota@starkey.co.uk**

London & South East
Sally Butcher
Mobile: **07706 330 334**
Email: **sally_butcher@starkey.co.uk**

South West
Lorraine Morley
Mobile: **07894 608 286**
Email: **lorraine_morley@starkey.co.uk**



Starkey

A global company headquartered in Eden Prairie, Minnesota, USA.

Starkey, William F. Austin House, Bramhall Technology Park,
Pepper Road, Hazel Grove, Stockport, SK7 5BX

T: **0800 042 0000** E: **sales@starkey.co.uk**
W: **www.starkey.co.uk / www.starkeypro.co.uk**

© 2023 Starkey Laboratories Ltd. Registered in England, No. 2691952.
Registered address: The Pinnacle, 170 Midsummer Boulevard, Milton Keynes, Buckinghamshire, MK9 1FE.

906108166: Last amended June 2023